

Six Room Audio Package



Essentia 6 Sound Sources, 6 Listening Zones, and the Next Wave in Digital Technology
Welcome to Generation D.

Essentia delivers the startlingly clear sound of NuVo from up to six different sources, and to six different listening zones in the house. It's diverse, expandable, and surprisingly affordable. And now, Essentia features Generation D design protocol-pure digital audio delivering energy conservation, lower heat generation, and clear, precise sound throughout your home.

Essentia's bidirectional RS232 port means it is completely controllable by home automation devices designed to control all aspects of the home. This is just one of the many features that make Essentia an incredible value for the home audio market.

A Single-Box Solution by NuVo
Essentia comes complete with the following:

- Essentia six-source, six-zone Generation D amplification.
- Six keypads with 36 replacement buttons
- White, ivory, and almond cover plates for each keypad
- RC2 remote control with batteries
- EZ-Port, Network cable, and four infrared emitters



DCM In-ceiling speakers are designed for every room in your home. Fill your halls, bedrooms and other areas with the rich sound only DCM can offer. Swivel mount tweeters let you point the sound toward your listening area for superior high frequency reproduction.

Variable tweeter level control on PC board offers custom tailored sound quality

Swivel mounted silk dome tweeter provides good sonic performance, and can be aimed to accommodate non-ideal mounting locations

Swivel style mounting dogs are factory positioned for easy installation

Fine steel mesh grilles with cloth insert, and black baffle will blend with home decor

High-performance crossover, featuring PTC tweeter protection provides consistent, reliable sound quality

Nickel plated compression terminals

Hole providers and Pre-construction kits.



C520 Specifications

Tweeter 20mm soft dome

Woofer 5-1/4" polypropylene

Power Handling 50 Watts RMS, 100 Watts Total

Sensitivity 85 dB (@1w/1m)

Frequency Range 60Hz-20kHz

Mounting Depth 3-1/2"

Dimensions 7-13/16" Dia. x 3-3/4"

Shipping Weight 5 lbs

Cut out size 6-1/2"

Nominal Impedance 8 Ω